

# Safety Matters **Construction**

Provided by: SCS Agency Inc

## Fall Protection: Guardrails

According to the Occupational Safety and Health Administration (OSHA), falls from elevation account for the majority of fatalities within the construction industry—with over 300 fatal falls occurring each year. That's why having adequate fall protection is crucial when working from height.

OSHA standards require some form of fall protection (e.g., guardrails, safety nets or fall arrest systems) to be in place at construction sites with vertical drops of 6 feet or more—except for certain tasks, such as scaffolding, in which vertical drops must exceed 10 feet before protection is needed. The type of fall protection necessary depends on several site features and the nature of work being performed.

As an employee, it's important to understand the different fall protection methods that you may encounter on the job. In particular, guardrails are stationary safety barriers that can help deter access to vertical drops—thus minimizing the risk of falls at the worksite. Review this guidance to learn more about guardrails as a means of fall protection.

### Guardrail Expectations

Put simply, guardrails are specially designed barriers aimed at keeping employees like you safely distanced from fall hazards on the job. In other words, guardrails are intended to help prevent falls from happening altogether, rather than protect you in the event that a fall occurs.

Under OSHA standards, guardrails must meet the following requirements:

- The height of the top railing in a guardrail must measure between 39 inches and 45

inches above the working surface, with the exception of certain situations (e.g., when the task at hand requires the use of stilts).

- Apart from the top railing, a guardrail must include additional protection in the form of one of these components:
  - **A middle railing**—Such a railing must be located midway between the top railing and the working surface.
  - **Mesh or screens**—These structures must extend from the top railing to the working surface, as well as across the openings between each railing support.
  - **Intermediate structures**—Such components (e.g., balusters) must be set up in a way that leaves the openings between each railing support no greater than 19 inches wide.
- The top railing in a guardrail must be able to withstand at least 200 pounds of force, without the railing deflecting downward to a height of less than 39 inches above the working surface when such force is applied. The middle railing, mesh, screens or intermediate structures in a guardrail must be capable of handling at least 150 pounds of force.
- Toe boards should be installed on any guardrail that presents the risk of worksite objects (e.g., tools or materials) falling on and potentially injuring anyone located below the elevated working surface.



- The components of a guardrail must be smooth to the touch, as rough or jagged surfaces could create other safety hazards (e.g., punctures or lacerations).

### Pros and Cons of Guardrails

Guardrails are a valuable form of fall protection that offers numerous advantages. In addition to minimizing fall hazards at the construction site, guardrails necessitate minimal safety training prior to implementation.

Compared to other methods of fall protection—such as safety nets and fall arrest systems—guardrails are particularly beneficial to employees like you, seeing as they don't require you to connect to any extra equipment (e.g., a harness) before working from height.

Also, other fall protection techniques are often only suitable for working from greater heights (e.g., more than 6 feet above the ground), whereas guardrails can be effective for working at a range of heights. Further, guardrails pose the lowest overall risk of fall-related injuries and deaths when ranked against other forms of fall protection.

However, guardrails are not a perfect fall protection solution. Although they require little training, guardrails can be more complicated and time-consuming to initially install at a worksite. As such, guardrails are often utilized at long-term project locations rather than at short-term worksites.

And, of course, it's still important to not solely rely on guardrails as a means of fall protection on the job. Rather, make sure to diligently follow all worksite safety policies and procedures related to fall prevention whenever you must work from height.

### Conclusion

In summary, guardrails can be a viable fall protection method in many circumstances. Keep in mind that a competent person should be in charge of determining what type of fall protection is necessary at the worksite. This decision will be based on specific site factors and what kind of work is being conducted.

If guardrails are selected as a means of fall protection at your worksite, be sure to play your part in promoting a safe work environment by routinely inspecting these guardrails for potential problems. Guardrail damages, noncompliance with OSHA's aforementioned guardrail requirements and any unaddressed fall hazards at the worksite should be reported immediately.

If you have questions or concerns related to guardrails or other fall protection methods on the job, be sure to consult your supervisor.